ISEKI TM TM3245F VRA/MVR/M (2011 AND AFTER)



ENGINE E3112-B34 Capacity: 2,7 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change every 10	0 hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Check every 10 hours, change every 10	0 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	
Check every 10 hours, change every 10	0 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Check every 10 hours, change every 10	0 hours	
USE	0 hours	CLIMATE
use First change only	0 hours	сымате Tropical
use First change only PRODUCT RECOMMENDATION 1	0 hours	
use First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 30	0 hours	
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours	0 hours	Tropical
USE First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE	0 hours	Tropical
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours use First change only	0 hours	Tropical
USE First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1	0 hours	Tropical
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20	0 hours	Tropical
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours	0 hours	CLIMATE Mediterranean
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours USE	0 hours	CLIMATE Mediterranean CLIMATE
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours USE First change only		CLIMATE Mediterranean
First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 30 Change every 50 hours USE First change only PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours USE	PRODUCT RECOMMENDATION 2 Multifleet SHPD 10W-40	CLIMATE Mediterranean CLIMATE

ISEKI TM TM3245F VRA/MVR/M (2011 AND AFTER)



USE	CLIMATE
First change only	Arctic
PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	
Change every 50 hours	·

DIFFERENTIAL FRONT Capacity: 4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 200 hours, change every 600 hours

TRANSAXLE HYDROSTATIC Capacity: 18 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 10 hours, change every 200 hours

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Change every 50 hours

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

information contained herein is subject to changes without notification.

ISEKI TM TM3245F VRA/MVR/M (2011 AND AFTER)



COOLING SYSTEM Capacity: 4,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours, change every	/ 600 hours/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the