

ISEKI TX/TXG TX 1000, F (1978-1992)



MOTOR KE55
Kapacitet: 2 liter

ANVEND
Normal

KLIMA
Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 30

PRODUKTANBEFALING 2

HDX 30

Skift alle 100 timer

ANVEND
Normal

KLIMA
Middelhavssagtigt

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Multifleet SHPD 10W-40

PRODUKTANBEFALING 3

Multifleet SCD 20W-20

Skift alle 100 timer

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Multifleet SCD 10W

PRODUKTANBEFALING 2

HDX 10W

Skift alle 100 timer

DIFFERENTIALE FOR (4x4)

Kapacitet: 0,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

Skift alle 300 timer

NAVREDUKTIONER FOR

Kapacitet: 0,25 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Gearlube GL-4 80W

Skift alle 300 timer

ISEKI TX/TXG TX 1000, F (1978-1992)

**TRANSAKSEL/HYDRAULISK SYSTEM 6/2**

Kapacitet: 9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

*Kontroller alle 100 timer, skift alle 300 timer***SMØREPUNKTER/NIPLER**

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

*Kontroller alle 50 timer***SMØREPUNKTER/NIPLER HJULLEJER FOR**

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

*Kontroller alle 900 timer***KØLESYSTEM**

Kapacitet: 4,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

*Skift alle 12 måneder***STYREHUS**

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.