

JCB FASTRAC 3000 SERIES FASTRAC 3200

TIER 4 (2013-2016)



ENGINE Sisu 74AWI Tier 4
Capacity: 25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Check every 10 hours, change every 500 hours/ 6 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Change every 100 hours

DIFFERENTIAL FRONT
Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

Check every 100 hours, change every 1000 hours/ 12 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

Change every 100 hours

DIFFERENTIAL REAR
Capacity: 27 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

Check every 100 hours, change every 1000 hours/ 12 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	

Change every 100 hours

JCB FASTRAC 3000 SERIES FASTRAC 3200 TIER 4 (2013-2016)



HUB REDUCTIONS FRONT

Capacity: 2,5 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Check every 100 hours, change every 500 hours/ 6 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90*Change every 100 hours*

RANGE AND PTO GEARBOX

Capacity: 47 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30*Check every 10 hours, change every 1000 hours/ 12 months*

HYDRAULIC SYSTEM

Capacity: 120 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Perlus H 46

PRODUCT RECOMMENDATION 2

Perlus AF 46*Check every 10 hours, change every 2000 hours/ 24 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 32

PRODUCT RECOMMENDATION 2

Perlus AF 32*Check every 10 hours, change every 2000 hours/ 24 months*

JCB FASTRAC 3000 SERIES FASTRAC 3200 TIER 4 (2013-2016)



HYDRAULIC BRAKE SYSTEM FRONT

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 10 hours, change every 2000 hours/ 24 months

HYDRAULIC BRAKE SYSTEM REAR

Capacity: 1-2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 10 hours, change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

Check every 50 hours

COOLING SYSTEM

Capacity: 27 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.