

# JOHN DEERE 1005 SERIES 1085 HYDRO/4 (1982-1989)



**MOTOR** John Deere 6466 AZ01  
Kapacitet: 16-20 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Tropisk |

PRODUKTANBEFALING 1

**Multifleet SCD 40**

*Kontroller alle 10 timer, skift alle 100 timer*

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Multifleet SCD 30**

*Kontroller alle 10 timer, skift alle 100 timer*

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Multifleet SHPD 15W-40**

*Kontroller alle 10 timer, skift alle 100 timer*

| ANVEND | KLIMA |
|--------|-------|
| Normal | Koldt |

PRODUKTANBEFALING 1

**Multifleet SCD 10W**

*Kontroller alle 10 timer, skift alle 100 timer*

**GEAR MANUEL** 4/4  
Kapacitet: 6,6 liter

| ANVEND | KLIMA            |
|--------|------------------|
| Normal | Middelhavsagtigt |

PRODUKTANBEFALING 1

**Gearlube GL-5 85W-140**

PRODUKTANBEFALING 2

**Unigear LS GL-3/GL-5 85W-140**

*Kontroller alle 100 timer, skift alle 500 timer*

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**SP Gear 5015**

PRODUKTANBEFALING 2

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 3

**Unigear HS GL-3/GL-5 80W-90**

*Kontroller alle 100 timer, skift alle 500 timer*

# JOHN DEERE 1005 SERIES 1085 HYDRO/4 (1982-1989)



## NAVREDUKTIONER FOR

Kapacitet: 2,1 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

**Gearlube GL-5 85W-140**

PRODUKTANBEFALING 2

**Unigear LS GL-3/GL-5 85W-140**

*Kontroller alle 100 timer, skift alle 500 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**SP Gear 5015**

PRODUKTANBEFALING 2

**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 3

**Unigear HS GL-3/GL-5 80W-90**

*Kontroller alle 100 timer, skift alle 500 timer*

## HYDRAULISK SYSTEM

Kapacitet: 20 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

PRODUKTANBEFALING 3

**Kroontrak MTH 10W-30**

*Kontroller alle 10 timer, skift alle 500 timer*

## HYDRAULISK SYSTEM HYDROSTATISK DREV

Kapacitet: 30 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**ATF-F (Ford)**

*Kontroller alle 10 timer, skift alle 500 timer*

## HYDRAULISK BREMSE- & KOBLINGSSYSTEM

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

PRODUKTANBEFALING 3

**Kroontrak MTH 10W-30**

*Kontroller alle 100 timer*

# JOHN DEERE 1005 SERIES 1085 HYDRO/4 (1982-1989)



## SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

*Kontroller alle 10 timer*

## KØLESYSTEM

Kapacitet: 34 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26**

*Kontroller alle 10 timer, skift alle 24 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*