

# JOHN DEERE 1100 SERIES 1174 SII (1991-1992)



**ENGINE** CD 6359 TZ003  
Capacity: 13 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>Multifleet SCD 40</b> | <b>Multifleet SCD 30</b> |  |

*Check every 10 hours, change every 200 hours/ 12 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|-----------------------------|-------------------------------|-------------------------------|
| <b>Kroontrak MTH 10W-30</b> | <b>Multifleet SHPD 10W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 10 hours, change every 200 hours/ 12 months*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Multifleet SCD 10W</b> |  |  |

*Check every 10 hours, change every 200 hours/ 12 months*

**CHAIN DRIVE CUTTING PLATFORM**  
Capacity: 0,5 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           | PRODUCT RECOMMENDATION 3     |
|-----------------------------|------------------------------------|------------------------------|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube GL-5 85W-140</b> |

*Check every 12 months/ 200 hours, change every 800 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
|--------------------------|--------------------------|---------------------------|
| <b>SP Gear 1011</b>      | <b>SP Gear 5015</b>      | <b>Syngear TDL 75W-90</b> |

*Check every 12 months/ 200 hours, change every 800 hours*

# JOHN DEERE 1100 SERIES 1174 SII (1991-1992)



## CYLINDER DRIVE REDUCTION

Capacity: 1,9 liter

| USE                         |                                    | CLIMATE                      |
|-----------------------------|------------------------------------|------------------------------|
| Normal                      |                                    | Mediterranean                |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           | PRODUCT RECOMMENDATION 3     |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube GL-5 85W-140</b> |

Check every 12 months/ 200 hours, change every 800 hours

| USE                      |                          | CLIMATE                   |
|--------------------------|--------------------------|---------------------------|
| Normal                   |                          | Moderate                  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
| <b>SP Gear 1011</b>      | <b>SP Gear 5015</b>      | <b>Syngear TDL 75W-90</b> |

Check every 12 months/ 200 hours, change every 800 hours

## HUB REDUCTIONS FRONT

Capacity: 2,2 liter

| USE                         |                                    | CLIMATE                      |
|-----------------------------|------------------------------------|------------------------------|
| Normal                      |                                    | Mediterranean                |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           | PRODUCT RECOMMENDATION 3     |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube GL-5 85W-140</b> |

Check every 12 months/ 200 hours, change every 800 hours

| USE                      |                          | CLIMATE                   |
|--------------------------|--------------------------|---------------------------|
| Normal                   |                          | Moderate                  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
| <b>SP Gear 1011</b>      | <b>SP Gear 5015</b>      | <b>Syngear TDL 75W-90</b> |

Check every 12 months/ 200 hours, change every 800 hours

## TRANSMISSION MANUAL 4/1

Capacity: 6,6 liter

| USE                         |                                    | CLIMATE                      |
|-----------------------------|------------------------------------|------------------------------|
| Normal                      |                                    | Mediterranean                |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           | PRODUCT RECOMMENDATION 3     |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> | <b>Gearlube GL-5 85W-140</b> |

Check every 12 months/ 200 hours, change every 800 hours

| USE                      |                          | CLIMATE                   |
|--------------------------|--------------------------|---------------------------|
| Normal                   |                          | Moderate                  |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3  |
| <b>SP Gear 1011</b>      | <b>SP Gear 5015</b>      | <b>Syngear TDL 75W-90</b> |

Check every 12 months/ 200 hours, change every 800 hours

# JOHN DEERE 1100 SERIES 1174 SII (1991-1992)



## HYDRAULIC SYSTEM

Capacity: 20 liter

| USE                              |                          | CLIMATE                     |
|----------------------------------|--------------------------|-----------------------------|
| Normal                           |                          | Moderate                    |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3    |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

Change every 400 hours

## HYDRAULIC SYSTEM HYDROSTATIC REEL DRIVE

Capacity: 10 liter

| USE                              |                          | CLIMATE                     |
|----------------------------------|--------------------------|-----------------------------|
| Normal                           |                          | Moderate                    |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3    |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

Change every 400 hours

## HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE                              |                          | CLIMATE                     |
|----------------------------------|--------------------------|-----------------------------|
| Normal                           |                          | Moderate                    |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3    |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

Check every 12 months/ 200 hours

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Check every 10 hours

## COOLING SYSTEM

Capacity: 30 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

Check every 12 months/ 200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.