

JOHN DEERE 300 SERIES 332 (1987-1992)

ENGINE Yanmar 3TN66
Capacity: 3 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SCD 40	Multifleet SCD 30

Change every 200 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40

Change every 200 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

Change every 200 hours

POWER TAKE OFF FRONT

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140

Check every 50 hours, change every 6 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 5015	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Check every 50 hours, change every 6 months

TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 4,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
ATF-F (Ford)	

Check every 10 hours, change every 200 hours

JOHN DEERE 300 SERIES 332 (1987-1992)**GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 50 hours

COOLING SYSTEM

Capacity: 2,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.