

JOHN DEERE 3000 SERIER 3400 (1995-1999)



MOTOR 4039 TRT35

Kapacitet: 11 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 40	Multifleet SCD 30	

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Armado Synth 5W-30	Multifleet SHPD 10W-40

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

DIFFERENTIALE FOR (4x4)

Kapacitet: 5,5 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 75W-90

Kontroller alle 250 timer, skift alle 1000 timer

KRAFTOVERFØRING FOR

Kapacitet: 0,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 50 timer, skift alle 250 timer

JOHN DEERE 3000 SERIER 3400 (1995-1999)



NAVREDUKTIONER FOR (4x4)

Kapacitet: 0,6 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 250 timer, skift alle 1000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 75W-90

Kontroller alle 250 timer, skift alle 1000 timer

TRANSAKSEL/HYDRAULISK SYSTEM

Kapacitet: 56 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 250 timer, skift alle 750 timer

SMØREPUNKTER/NIPLER AKSEL FOR

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

Kontroller alle 50 timer

SMØREPUNKTER/NIPLER ANDRE

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1		
MoS2 Grease EP 2		

Kontroller alle 250 timer

JOHN DEERE 3000 SERIER 3400 (1995-1999)



KØLESYSTEM

Kapacitet: 13,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 1500 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.