

# JOHN DEERE 4000 SERIER 4500 (2WD/4WD) PIN (150001-)(2000-2002)



**MOTOR** Yanmar 4TNE84  
Kapacitet: 4,8 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1

**Asyntho 5W-30**

PRODUKTANBEFALING 2

**Multifleet SHPD 15W-40**

*Kontroller alle 10 timer, skift alle 200 timer*

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

**Asyntho 5W-30**

PRODUKTANBEFALING 2

**Multifleet SHPD 15W-40**

*Skift alle 50 timer*

## DIFFERENTIALE FOR

Kapacitet: 7,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

*Kontroller alle 50 timer, skift alle 500 timer*

## TRANSAKSEL HYDROSTATISK/HYDRAULISK SYSTEM

Kapacitet: 33,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

*Kontroller alle 10 timer, skift alle 200 timer*

## TRANSAKSEL/HYDRAULISK SYSTEM

Kapacitet: 25,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

*Kontroller alle 10 timer, skift alle 200 timer*

# JOHN DEERE 4000 SERIER 4500 (2WD/4WD) PIN (150001-)(2000-2002)



## SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2**

*Kontroller alle 25 timer*

## KØLESYSTEM

Kapacitet: 6,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

PRODUKTANBEFALING 2

**Coolant -26**

*Kontroller alle 10 timer, skift alle 24 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*