

# JOHN DEERE 4000 SERIER 4610 PIN (160001-) (2002-2004)



**MOTOR** Yanmar 4TNE84  
Kapacitet: 4,8 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 2  
**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 3  
**Asyntho 5W-30**

*Kontroller alle 10 timer, skift alle 200 timer*

ANVEND  
Første skift kun

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agridiesel CRD+ 15W-40**

PRODUKTANBEFALING 2  
**Kroontrak MTH 10W-30**

PRODUKTANBEFALING 3  
**Asyntho 5W-30**

*Skift alle 50 timer*

**DIFFERENTIALE FOR**  
Kapacitet: 5 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2  
**Agrifluid HT-Plus**

*Kontroller alle 50 timer, skift alle 500 timer*

**TRANSAKSEL/HYDRAULISK SYSTEM**  
Kapacitet: 36,9 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2  
**Agrifluid HT-Plus**

*Kontroller alle 10 timer, skift alle 400 timer*

**SMØREPUNKTER/NIPLER**

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Labora Grease**

PRODUKTANBEFALING 2  
**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3  
**MP Lithep Grease EP 2**

*Kontroller alle 50 timer*

# JOHN DEERE 4000 SERIER 4610 PIN (160001-)(2002-2004)



## KØLESYSTEM

Kapacitet: 6,1 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

### PRODUKTANBEFALING 2

**Coolant -26**

*Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*