

JOHN DEERE 4000 SERIES 4310 PIN (130001-)(2002-2004)



ENGINE Yanmar 3TNE84
Capacity: 4,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-----------------------------|--------------------------|
| Agridiesel CRD+ 15W-40 | Kroontrak MTH 10W-30 | Asyntho 5W-30 |

Check every 10 hours, change every 200 hours

| USE | CLIMATE |
|-------------------|----------|
| First change only | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-----------------------------|--------------------------|
| Agridiesel CRD+ 15W-40 | Kroontrak MTH 10W-30 | Asyntho 5W-30 |

Change every 50 hours

DIFFERENTIAL FRONT
Capacity: 4,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|----------------------------------|--------------------------|--|
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | |

Check every 50 hours, change every 500 hours

TRANSAXLE/HYDRAULIC SYSTEM
Capacity: 24 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|----------------------------------|--------------------------|--|
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | |

Check every 10 hours, change every 400 hours

GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------------|------------------------------|
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 50 hours

JOHN DEERE 4000 SERIES 4310 PIN (130001-)(2002-2004)

**COOLING SYSTEM**

Capacity: 5,7 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.