

JOHN DEERE 50 SERIES 2350 (1986-1995)



MOTOR

Kapacitet: 8,5 liter, Filterkapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 40

Kontroller alle 10 timer, skift alle 200 timer

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SCD 30

Kontroller alle 10 timer, skift alle 200 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Multifleet SHPD 10W-40

PRODUKTANBEFALING 3

Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 200 timer

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Multifleet SCD 10W

Kontroller alle 10 timer, skift alle 200 timer

DIFFERENTIALE FOR (4x4)

Kapacitet: 5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 100 timer, skift alle 1000 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-5 80W-90

PRODUKTANBEFALING 3

Unigear HS GL-3/GL-5 80W-90

Kontroller alle 100 timer, skift alle 1000 timer

JOHN DEERE 50 SERIES 2350 (1986-1995)



NAVREDUKTIONER FOR (4x4)

Kapacitet: 0,75 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Kontroller alle 100 timer, skift alle 1000 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Kontroller alle 100 timer, skift alle 1000 timer

TRANSAKSEL/HYDRAULISK SYSTEM 8/4

Kapacitet: 33 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 50 timer, skift alle 1000 timer

HYDRAULISK KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 50 timer, skift alle 24 måneder

SMØREPUNKTER/NIPLER AKSEL FOR

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 50 timer

JOHN DEERE 50 SERIES 2350 (1986-1995)



SMØREPUNKTER/NIPLER ANDRE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 50 timer

SMØREPUNKTER/NIPLER HJULLEJER BAG

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 8 timer, skift alle 500 timer

SMØREPUNKTER/NIPLER HJULLEJER FOR

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 1000 timer

SMØREPUNKTER/NIPLER KOBLINGSUDRYKKERLEJE

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 100 timer

SMØREPUNKTER/NIPLER TREPUNKSTOPHÆNGET

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 200 timer

JOHN DEERE 50 SERIES 2350 (1986-1995)



KØLESYSTEM

Kapacitet: 13-15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.