

**JOHN DEERE 50 SERIES 4350 (1986-1995)****ENGINE**

Capacity: 19 liter, Filter capacity: 0,5 liter

**USE**

Normal

**CLIMATE**

Tropical

**PRODUCT RECOMMENDATION 1****Multifleet SCD 40***Check every 10 hours, change every 200 hours***USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Multifleet SCD 30***Check every 10 hours, change every 200 hours***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 2****Multifleet SHPD 10W-40****PRODUCT RECOMMENDATION 3****Multifleet SHPD 15W-40***Check every 10 hours, change every 200 hours***USE**

Normal

**CLIMATE**

Cold

**PRODUCT RECOMMENDATION 1****Multifleet SCD 10W***Check every 10 hours, change every 200 hours***DIFFERENTIAL FRONT (4x4)**

Capacity: 9,5 liter

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Gearlube GL-5 85W-140****PRODUCT RECOMMENDATION 2****Unigear LS GL-3/GL-5 85W-140***Check every 100 hours, change every 1000 hours***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 5015****PRODUCT RECOMMENDATION 2****Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 3****Unigear HS GL-3/GL-5 80W-90***Check every 100 hours, change every 1000 hours*

**JOHN DEERE 50 SERIES 4350 (1986-1995)****HUB REDUCTIONS FRONT (4x4)**

Capacity: 1,75 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

*Check every 100 hours, change every 1000 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 5015</b>	<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>

*Check every 100 hours, change every 1000 hours***TRANSAXLE/HYDRAULIC SYSTEM 16/8**

Capacity: 65 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 50 hours, change every 1000 hours***HYDRAULIC CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Check every 50 hours, change every 24 months***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 50 hours*

**JOHN DEERE 50 SERIES 4350 (1986-1995)****GREASE POINTS/NIPPLES 3-POINT HITCH**

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Labora Grease</b>	PRODUCT RECOMMENDATION 2 <b>Q5 MP Calcep Grease EP 2</b>	PRODUCT RECOMMENDATION 3 <b>MP Lithep Grease EP 2</b>

*Check every 200 hours*

**GREASE POINTS/NIPPLES CLUTCH RELEASE BEARING**

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Labora Grease</b>	PRODUCT RECOMMENDATION 2 <b>Q5 MP Calcep Grease EP 2</b>	PRODUCT RECOMMENDATION 3 <b>MP Lithep Grease EP 2</b>

*Check every 100 hours*

**GREASE POINTS/NIPPLES OTHERS**

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Labora Grease</b>	PRODUCT RECOMMENDATION 2 <b>Q5 MP Calcep Grease EP 2</b>	PRODUCT RECOMMENDATION 3 <b>MP Lithep Grease EP 2</b>

*Check every 50 hours*

**GREASE POINTS/NIPPLES WHEEL BEARINGS REAR**

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Labora Grease</b>	PRODUCT RECOMMENDATION 2 <b>Q5 MP Calcep Grease EP 2</b>	PRODUCT RECOMMENDATION 3 <b>MP Lithep Grease EP 2</b>

*Check every 8 hours, change every 500 hours*

**COOLING SYSTEM**

Capacity: 26 liter

USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 <b>Coolant -38 Organic NF</b>	PRODUCT RECOMMENDATION 2 <b>Coolant -26</b>	

*Check every 10 hours, change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*