

JOHN DEERE 5015 F/V SERIES 5515F/V (2003-2008)



MOTOR John Deere 4045 TAT
Kapacitet: 8 liter

ANVEND

Forlænget

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

DIFFERENTIALE FOR

Kapacitet: 5 liter (F type), Kapacitet: 3,8 liter (V type)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer

NAVREDUKTIONER FOR

Kapacitet: 0,5 liter (F type), Kapacitet: 0,6 liter (V type)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer

TRANSAKSEL/HYDRAULISK SYSTEM

Kapacitet: 2 liter (+ forhjulstræk), Kapacitet: 37 liter (12x12), Kapacitet: 36 liter (24x12), Kapacitet: 46 liter (24x24)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 1250 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0,32 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer

JOHN DEERE 5015 F/V SERIES 5515F/V (2003-2008)



SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 50 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gear Grease EP 1		

Kontroller alle 50 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Gear Grease EP 0		

Kontroller alle 50 timer

KØLESYSTEM

Kapacitet: 13 liter (+ kabine), Kapacitet: 12 liter (Uten hytte)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.