

JOHN DEERE 5020 SERIES 5720 (2003-2008)



MOTOR John Deere 4045 TL273
Kapacitet: 13 liter

ANVEND	KLIMA
Forlænget	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Agrisynth MSP 10W-40	AgriDiesel MSP 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak CVT 10W-40	Agrisynth MSP 10W-40	AgriDiesel MSP 15W-40

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

DIFFERENTIALE FOR
Kapacitet: 4,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer/ 24 måneder

KRAFTOVERFØRING FOR
Kapacitet: 3,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

NAVREDUKTIONER FOR
Kapacitet: 0,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer/ 24 måneder

JOHN DEERE 5020 SERIES 5720 (2003-2008)**TRANSAXSEL/HYDRAULISK SYSTEM 16/16**

Kapacitet: 1 liter (+ reduktionsgear), Kapacitet: 50 liter (PowrQuad), Kapacitet: 51 liter (PowrQuad Plus)

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Agrifluid Synth XHP Ultra	PRODUKTANBEFALING 2 Agrifluid HT-Plus	PRODUKTANBEFALING 3 Kroontrak MTH 10W-30

*Kontroller alle 250 timer, skift alle 1500 timer/ 24 måneder***SMØREPUNKTER/NIPLER**

ANVEND Normal		KLIMA Middelhavssagtigt
PRODUKTANBEFALING 1 Labora Grease	PRODUKTANBEFALING 2 Q5 MP Calcep Grease EP 2	PRODUKTANBEFALING 3 MP Lithep Grease EP 2

Kontroller alle 50 timer

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Gear Grease EP 1		

Kontroller alle 50 timer

ANVEND Normal		KLIMA Koldt
PRODUKTANBEFALING 1 Gear Grease EP 0		

*Kontroller alle 50 timer***KØLESYSTEM**

Kapacitet: 13,5 liter

ANVEND Normal		KLIMA Moderat
PRODUKTANBEFALING 1 Coolant -38 Organic NF	PRODUKTANBEFALING 2 Coolant -26	

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.