## **JOHN DEERE 6000 SERIES 6300 (4X4)** (1992-1997)



| ENGINE<br>Capacity: 12 liter                            |                          |                          |
|---|--------------------------|--------------------------|
| USE   |                          | CLIMATE                  |
| Normal  |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1                                | PRODUCT RECOMMENDATION 2 |                          |
| Multifleet SCD 40                                       | Multifleet SCD 30        |                          |
| Check every 10 hours, change every 250 hours/ 12 months |                          |                          |
| USE   |                          | CLIMATE                  |
| Normal  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                                | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30                                    | Multifleet SHPD 10W-40   | Multifleet SHPD 15W-40   |
| Check every 10 hours, change every 250 hours/ 12 months |                          |                          |
| USE   |                          | CLIMATE                  |
| Normal  |                          | Cold                     |
| PRODUCT RECOMMENDATION 1                                |                          |                          |
| Multifleet SCD 10W                                      |                          |                          |
| Check every 10 hours, change every 250 l                | hours/ 12 months         |                          |

| <b>DIFFERENTIAL FRONT</b> (4x4)<br>Capacity: 6,75 liter |                              |               |
|---|------------------------------|---------------|
| USE   |                              | CLIMATE       |
| Normal  |                              | Mediterranean |
| PRODUCT RECOMMENDATION 1                                | PRODUCT RECOMMENDATION 2     |               |
| Gearlube GL-5 85W-140                                   | Unigear LS GL-3/GL-5 85W-140 |               |
| 01 1 0501 1 150   |                              |               |

Check every 250 hours, change every 1500 hours/ 24 months

| use<br>Normal            |                          | climate<br>Moderate      |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011             | Syngear TDL 75W-90       | Gearlube HS GL-5 75W-90  |

Check every 250 hours, change every 1500 hours/ 24 months

## **JOHN DEERE 6000 SERIES 6300 (4X4)** (1992-1997)



| HUB REDUCTIONS FRONT (4x4)<br>Capacity: 1 liter           |                              |                          |
|---|------------------------------|--------------------------|
| USE   |                              | CLIMATE                  |
| Normal  |                              | Mediterranean            |
| PRODUCT RECOMMENDATION 1                                  | PRODUCT RECOMMENDATION 2     |                          |
| Gearlube GL-5 85W-140                                     | Unigear LS GL-3/GL-5 85W-140 |                          |
| Check every 250 hours, change every 1500 hours/ 24 months |                              |                          |
| USE   |                              | CLIMATE                  |
| Normal  |                              | Moderate                 |
| PRODUCT RECOMMENDATION 1                                  | PRODUCT RECOMMENDATION 2     | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011  | Syngear TDL 75W-90           | Gearlube HS GL-5 75W-90  |

Check every 250 hours, change every 1500 hours/24 months

|                          | CLIMATE                  |
|--------------------------|--------------------------|
|                          | Moderate                 |
| PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus        | Kroontrak MTH 10W-30     |
|                          |                          |

Check every 250 hours, change every 1500 hours/ 24 months

| GREASE POINTS/NIPPLES    |               |
|--------------------------|---------------|
| USE                      | CLIMATE       |
| Normal                   | Mediterranean |
| PRODUCT RECOMMENDATION 1 |               |
| MoS2 Grease EP 2         |               |
|                          | :             |

Check every 250 hours

| COOLING SYSTEM<br>Capacity: 17,5 liter                   |                          |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal   |                          | Moderate |
| PRODUCT RECOMMENDATION 1                                 | PRODUCT RECOMMENDATION 2 |          |
| Coolant -38 Organic NF                                   | Coolant -26              |          |
| Check every 10 hours, change every 1500 hours/ 24 months |                          |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.