

JOHN DEERE 6020 SERIES 6220 TIER II (NR. 398791 ->) (2003-2005)



ENGINE John Deere 4045 TL272
Capacity: 16 liter

| USE | CLIMATE |
|----------|----------|
| Extended | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|------------------------------|
| Agrisynth LSP 10W-40 | Agrisynth MSP 10W-40 | Agridiesel MSP 15W-40 |

Check every 10 hours, change every 500 hours/ 12 months

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-----------------------------|------------------------------|
| Kroontrak CVT 10W-40 | Agrisynth MSP 10W-40 | Agridiesel MSP 15W-40 |

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT
Capacity: 6,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|----------------------------------|--------------------------|-----------------------------|
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 250 hours, change every 1500 hours/ 24 months

HUB REDUCTIONS FRONT
Capacity: 0,9 liter (+ front brakes), Capacity: 0,6 liter (Without brakes)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|----------------------------------|--------------------------|-----------------------------|
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 250 hours, change every 750 hours

POWER TAKE OFF FRONT
Capacity: 3,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|----------------------------------|--------------------------|-----------------------------|
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 250 hours, change every 1500 hours/ 24 months

JOHN DEERE 6020 SERIES 6220 TIER II (NR. 398791 ->) (2003-2005)



TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 1 liter (+ crawler gear), Capacity: 3 liter (+ TLS axle), Capacity: 60 liter (AutoPowr), Capacity: 50 liter (PowrQuad), Capacity: 52 liter (SynchroPlus/Power Reverser)

| | | |
|---------------|--|---------------------|
| USE Normal | | CLIMATE Moderate |
|---------------|--|---------------------|

| | | |
|--------------------------------------------------------------|------------------------------------------------------|---------------------------------------------------------|
| PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra | PRODUCT RECOMMENDATION 2 Agrifluid HT-Plus | PRODUCT RECOMMENDATION 3 Kroontrak MTH 10W-30 |
|--------------------------------------------------------------|------------------------------------------------------|---------------------------------------------------------|

Check every 250 hours, change every 1500 hours/ 24 months

GREASE POINTS/NIPPLES

| | | |
|---------------|--|--------------------------|
| USE Normal | | CLIMATE Mediterranean |
|---------------|--|--------------------------|

| | | |
|--------------------------------------------------|-------------------------------------------------------------|----------------------------------------------------------|
| PRODUCT RECOMMENDATION 1 Labora Grease | PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2 | PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2 |
|--------------------------------------------------|-------------------------------------------------------------|----------------------------------------------------------|

Check every 50 hours

| | | |
|---------------|--|---------------------|
| USE Normal | | CLIMATE Moderate |
|---------------|--|---------------------|

| | | |
|-----------------------------------------------------|--|--|
| PRODUCT RECOMMENDATION 1 Gear Grease EP 1 | | |
|-----------------------------------------------------|--|--|

Check every 50 hours

| | | |
|---------------|--|-----------------|
| USE Normal | | CLIMATE Cold |
|---------------|--|-----------------|

| | | |
|-----------------------------------------------------|--|--|
| PRODUCT RECOMMENDATION 1 Gear Grease EP 0 | | |
|-----------------------------------------------------|--|--|

Check every 50 hours

COOLING SYSTEM

Capacity: 13,5 liter (+ cabin), Capacity: 24 liter (+ intercooler), Capacity: 11 liter (Without cabin)

| | | |
|---------------|--|---------------------|
| USE Normal | | CLIMATE Moderate |
|---------------|--|---------------------|

| | | |
|-----------------------------------------------------------|------------------------------------------------|--|
| PRODUCT RECOMMENDATION 1 Coolant -38 Organic NF | PRODUCT RECOMMENDATION 2 Coolant -26 | |
|-----------------------------------------------------------|------------------------------------------------|--|

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.