

# JOHN DEERE 6030 SERIES (PREMIUM) 6430 (2009-2014)



**MOTOR** John Deere 4045 HL281  
Kapacitet: 16 liter

| ANVEND                                      | KLIMA   |
|---------------------------------------------|---------|
| Udvidet, svovlniveau i brændstof 0-2000 ppm | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2          | PRODUKTANBEFALING 3           |
|-----------------------------|------------------------------|-------------------------------|
| <b>Agrisynth LSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> |

Kontroller alle 10 timer, skift alle 500 timer

| ANVEND                                         | KLIMA   |
|------------------------------------------------|---------|
| Udvidet, sulfoniveau i brændstof 2000-5000 ppm | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2          | PRODUKTANBEFALING 3           |
|-----------------------------|------------------------------|-------------------------------|
| <b>Agrisynth LSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> |

Kontroller alle 10 timer, skift alle 300 timer

| ANVEND                                         | KLIMA   |
|------------------------------------------------|---------|
| Normalt, sulfoniveau i brændstof 2000-5000 ppm | Moderat |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
|------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Kontroller alle 10 timer, skift alle 200 timer

| ANVEND                                     | KLIMA   |
|--------------------------------------------|---------|
| Normal, svovlniveau i brændstof 0-2000 ppm | Moderat |

| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2           | PRODUKTANBEFALING 3           |
|------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Kontroller alle 10 timer, skift alle 250 timer

**DIFFERENTIALE FOR**  
Kapacitet: 6,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
|----------------------------------|--------------------------|-----------------------------|
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

Kontroller alle 250 timer, skift alle 1500 timer/ 24 måneder

**KRAFTOVERFØRING FOR**  
Kapacitet: 3,5 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
|----------------------------------|--------------------------|-----------------------------|
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

Kontroller alle 250 timer, skift alle 1500 timer/ 24 måneder

# JOHN DEERE 6030 SERIES (PREMIUM) 6430 (2009-2014)



## NAVREDUKTIONER FOR

Kapacitet: 0,6 liter, Kapacitet: 0,9 liter (+ forbremses)

| ANVEND                           |                          | KLIMA                       |
|----------------------------------|--------------------------|-----------------------------|
| Normal                           |                          | Moderat                     |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

Kontroller alle 250 timer, skift alle 750 timer

## TRANSAKSEL/HYDRAULISK SYSTEM

Kapacitet: 49-52 liter, Kapacitet: 3 liter (+ forhjulstræk), Kapacitet: 1 liter (+ krybegear), Kapacitet: 3 liter (+ TLS aksel)

| ANVEND                           |                          | KLIMA                       |
|----------------------------------|--------------------------|-----------------------------|
| Normal                           |                          | Moderat                     |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

Kontroller alle 250 timer, skift alle 1500 timer/ 24 måneder

## SMØREPUNKTER/NIPLER

| ANVEND               |                                 | KLIMA                        |
|----------------------|---------------------------------|------------------------------|
| Normal               |                                 | Middelhavsagtigt             |
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Skift alle 50 timer

| ANVEND                  |  | KLIMA   |
|-------------------------|--|---------|
| Normal                  |  | Moderat |
| PRODUKTANBEFALING 1     |  |         |
| <b>Gear Grease EP 1</b> |  |         |

Skift alle 50 timer

| ANVEND                  |  | KLIMA |
|-------------------------|--|-------|
| Normal                  |  | Koldt |
| PRODUKTANBEFALING 1     |  |       |
| <b>Gear Grease EP 0</b> |  |       |

Skift alle 50 timer

# JOHN DEERE 6030 SERIES (PREMIUM) 6430 (2009-2014)



## KØLESYSTEM

Kapacitet: 26,5 liter, Kapacitet: 29 liter (+ kabine)

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Coolant SP 15+**

### PRODUKTANBEFALING 2

**Coolant SP 12**

### PRODUKTANBEFALING 3

**Coolant -38 Organic NF**

*Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*