

JOHN DEERE 6030 SERIES (PREMIUM) 6830 PREMIUM (2010-2014)



MOTOR John Deere 6068 HL487
Kapacitet: 19,5 liter

ANVEND	KLIMA
Udvidet, svovlniveau i brændstof 0-2000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Kontroller alle 10 timer, skift alle 500 timer

ANVEND	KLIMA
Udvidet, sulfoniveau i brændstof 2000-5000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Kontroller alle 10 timer, skift alle 300 timer

ANVEND	KLIMA
Normalt, sulfoniveau i brændstof 2000-5000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof 0-2000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 250 timer

DIFFERENTIALE FOR
Kapacitet: 8,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer/ 24 måneder

KRAFTOVERFØRING FOR
Kapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer/ 24 måneder

JOHN DEERE 6030 SERIES (PREMIUM) 6830 PREMIUM (2010-2014)



NAVREDUKTIONER FOR

Kapacitet: 1,7 liter, Kapacitet: 2,6 liter (+ forbremses)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 750 timer

TRANSAKSEL/HYDRAULISK SYSTEM

Kapacitet: 3 liter (+ forhjulstræk), Kapacitet: 1 liter (+ krybegear), Kapacitet: 3 liter (+ TLS aksel), Kapacitet: 66 liter (AutoPowr), Kapacitet: 14 liter (med ekstra oiletank), Kapacitet: 56 liter (PowrQuad Plus/AutoQuad Plus)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer/ 24 måneder

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Grease EP 1		

Skift alle 50 timer

ANVEND		KLIMA
Normal		Koldt
PRODUKTANBEFALING 1		
Gear Grease EP 0		

Skift alle 50 timer

JOHN DEERE 6030 SERIES (PREMIUM) 6830 PREMIUM (2010-2014)



KØLESYSTEM

Kapacitet: 33,6 liter (+ kabine)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.