

JOHN DEERE 6MC/RC SERIES 6100RC (EU)

TIER 4 / STAGE IIIB (2013-2016)



MOTOR John Deere 6068 HL490
Kapacitet: 17,1 liter

ANVEND

Biodiesel B20

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 125 timer/ 12 måneder

ANVEND

Normalt, svovlniveau i brændstof <15 ppm

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

DIFFERENTIALE FOR Standard MFWD
Kapacitet: 8,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer

KRAFTOVERFØRING FOR
Kapacitet: 2,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Skift alle 1500 timer

NAVREDUKTIONER FOR Standard MFWD
Kapacitet: 1,7 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer

JOHN DEERE 6MC/RC SERIES 6100RC (EU)

TIER 4 / STAGE IIIB (2013-2016)



TRANSAXSEL/HYDRAULISK SYSTEM

Kapacitet: 52 liter, Kapacitet: 3 liter (+ forhjulstræk), Kapacitet: 1 liter (med krybegear)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 1500 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Gear Grease EP 1		

Skift alle 50 timer

ANVEND		KLIMA
Normal		Koldt
PRODUKTANBEFALING 1		
Gear Grease EP 0		

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 28,2 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.