

# JOHN DEERE 6R SERIES 6175R (2014-2015)



**MOTOR** John Deere 6068 HL499  
Kapacitet: 23,5 liter

ANVEND

Biodiesel B20

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrisynth LSP Ultra FE 5W-30**

PRODUKTANBEFALING 2

**Agrisynth LSP Ultra 10W-40**

PRODUKTANBEFALING 3

**Agrisynth LSP 10W-40**

*Kontroller alle 10 timer, skift alle 125 timer/ 12 måneder*

ANVEND

Normal, svovlniveau i brændstof <15 ppm

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrisynth LSP Ultra FE 5W-30**

PRODUKTANBEFALING 2

**Agrisynth LSP Ultra 10W-40**

PRODUKTANBEFALING 3

**Agrisynth LSP 10W-40**

*Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder*

## DIFFERENTIALE FOR

Kapacitet: 8,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

PRODUKTANBEFALING 3

**Kroontrak MTH 10W-30**

*Kontroller alle 250 timer, skift alle 1500 timer*

## KRAFTOVERFØRING FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

PRODUKTANBEFALING 3

**Kroontrak MTH 10W-30**

## NAVREDUKTIONER FOR

Kapacitet: 2,6 liter (Med bremsen), Kapacitet: 1,7 liter (Uden bremsen)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

PRODUKTANBEFALING 3

**Kroontrak MTH 10W-30**

*Kontroller alle 250 timer, skift alle 1500 timer*

## JOHN DEERE 6R SERIES 6175R (2014-2015)

**TRANSAKSEL/HYDRAULISK SYSTEM**

Kapacitet: 28 liter (+ ekstra reservoir), Kapacitet: 81 liter (AutoPowr), Kapacitet: 75 liter (DirectDrive), Kapacitet: 71 liter (PowrQuad Plus/AutoQuad Plus)

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2  
**Agrifluid HT-Plus**

PRODUKTANBEFALING 3  
**Kroontrak MTH 10W-30**

*Kontroller alle 10 timer, skift alle 1500 timer*

**SMØREPUNKTER/NIPLER**

ANVEND  
Normal

KLIMA  
Middelhavsagtigt

PRODUKTANBEFALING 1  
**Labora Grease**

PRODUKTANBEFALING 2  
**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3  
**MP Lithep Grease EP 2**

*Skift alle 50 timer*

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gear Grease EP 1**

*Skift alle 50 timer*

ANVEND  
Normal

KLIMA  
Koldt

PRODUKTANBEFALING 1  
**Gear Grease EP 0**

*Skift alle 50 timer*

**KØLESYSTEM**

Kapacitet: 28,2 liter

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Coolant -38 Organic NF**

PRODUKTANBEFALING 2  
**Coolant -26**

*Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder*

**SCR (SELECTIVE CATALYTIC REDUCTION)-SYSTEM**

Kapacitet: 20 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*