

JOHN DEERE 6R SERIES 6215R (2014-2015)

ENGINE John Deere 6068 HL501
Capacity: 23,5 liter

USE Biodiesel B20		CLIMATE Moderate
-----------------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP Ultra FE 5W-30	PRODUCT RECOMMENDATION 2 Agrisynth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40
------------------------------------------------------------------------	----------------------------------------------------------------------	----------------------------------------------------------------

Check every 10 hours, change every 125 hours/ 12 months

USE Normal, fuel sulfur level <15 ppm		CLIMATE Moderate
-------------------------------------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP Ultra FE 5W-30	PRODUCT RECOMMENDATION 2 Agrisynth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 3 Agrisynth LSP 10W-40
------------------------------------------------------------------------	----------------------------------------------------------------------	----------------------------------------------------------------

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT

Capacity: 8,2 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra	PRODUCT RECOMMENDATION 2 Agrifluid HT-Plus	PRODUCT RECOMMENDATION 3 Kroontrak MTH 10W-30
---------------------------------------------------------------------	-------------------------------------------------------------	----------------------------------------------------------------

Check every 250 hours, change every 1500 hours

HUB REDUCTIONS FRONT

Capacity: 2,6 liter (With brakes), Capacity: 1,7 liter (Without brakes)

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra	PRODUCT RECOMMENDATION 2 Agrifluid HT-Plus	PRODUCT RECOMMENDATION 3 Kroontrak MTH 10W-30
---------------------------------------------------------------------	-------------------------------------------------------------	----------------------------------------------------------------

Check every 250 hours, change every 1500 hours

POWER TAKE OFF FRONT

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra	PRODUCT RECOMMENDATION 2 Agrifluid HT-Plus	PRODUCT RECOMMENDATION 3 Kroontrak MTH 10W-30
---------------------------------------------------------------------	-------------------------------------------------------------	----------------------------------------------------------------

JOHN DEERE 6R SERIES 6215R (2014-2015)**TRANSAXLE/HYDRAULIC SYSTEM**

Capacity: 28 liter (+ additional reservoir), Capacity: 81 liter (AutoPowr), Capacity: 75 liter (DirectDrive), Capacity: 71 liter (PowrQuad Plus/AutoQuad Plus)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 10 hours, change every 1500 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

Change every 50 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		

Change every 50 hours

COOLING SYSTEM

Capacity: 28,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 2000 hours/ 24 months

SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR)

Capacity: 20 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.