

JOHN DEERE 7020 SERIES 7720 (2004-2007)



MOTOR 6.8
Kapacitet: 26 liter

ANVEND
Forlænget

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrisynth LSP 10W-40

PRODUKTANBEFALING 2
Agrisynth MSP 10W-40

PRODUKTANBEFALING 3
Agridiesel MSP 15W-40

Kontroller alle 10 timer, skift alle 500 timer/ 12 måneder

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Kroontrak CVT 10W-40

PRODUKTANBEFALING 2
Agrisynth MSP 10W-40

PRODUKTANBEFALING 3
Agridiesel MSP 15W-40

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

DIFFERENTIALE FOR
Kapacitet: 14,4 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2
Agrifluid HT-Plus

PRODUKTANBEFALING 3
Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer/ 24 måneder

KRAFTOVERFØRING FOR
Kapacitet: 8 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2
Agrifluid HT-Plus

PRODUKTANBEFALING 3
Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer/ 24 måneder

NAVREDUKTIONER FOR
Kapacitet: 3,8 liter (Heavy Duty), Kapacitet: 1,9 liter (Standard)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2
Agrifluid HT-Plus

PRODUKTANBEFALING 3
Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer/ 24 måneder

**TRANSAKSEL/HYDRAULISK SYSTEM**

Kapacitet: 108 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30*Kontroller alle 10 timer, skift alle 1500 timer/ 24 måneder***SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Gear Grease EP 1

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Gear Grease EP 0**KØLESYSTEM**

Kapacitet: 32 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.