

JOHN DEERE 7030 SERIES (PREMIUM) 7230 PREMIUM (2008-2011)



ENGINE John Deere 6068 HRW72
Capacity: 19,5 liter

USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours/ 12 months

ENGINE John Deere 6068 HRW73
Capacity: 19,5 liter

USE		CLIMATE
Extended		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT
Capacity: 8,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 250 hours, change every 1500 hours/ 24 months

JOHN DEERE 7030 SERIES (PREMIUM) 7230 PREMIUM (2008-2011)



DIFFERENTIAL REAR Hi-Crop

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Gearlube HS GL-5 75W-90

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

HUB REDUCTIONS FRONT

Capacity: 1,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 250 hours, change every 750 hours

POWER TAKE OFF FRONT

Capacity: 3,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 250 hours, change every 1500 hours

TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 1 liter (+ crawler gear), Capacity: 3 liter (+ front wheel drive), Capacity: 3 liter (+ TLS axle), Capacity: 60 liter (IVT transmission), Capacity: 52 liter (PowrQuad Plus/AutoQuad Plus), Capacity: 52 liter (SynchroPlus/Power Reverser)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 250 hours, change every 1500 hours/ 24 months

JOHN DEERE 7030 SERIES (PREMIUM) 7230 PREMIUM (2008-2011)



GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

Change every 50 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Gear Grease EP 0		

Change every 50 hours

COOLING SYSTEM

Capacity: 24 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.