

# JOHN DEERE 7R SERIES 7215R IPM (EU) (2012-2016)



**MOTOR** John Deere PowerTech PSX Stage 4i  
Kapacitet: 24,5 liter

|               |         |
|---------------|---------|
| ANVEND        | KLIMA   |
| Biodiesel B20 | Moderat |

|                                     |                                   |                             |
|-------------------------------------|-----------------------------------|-----------------------------|
| PRODUKTANBEFALING 1                 | PRODUKTANBEFALING 2               | PRODUKTANBEFALING 3         |
| <b>Agrisynth LSP Ultra FE 5W-30</b> | <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> |

*Kontroller alle 10 timer, skift alle 125 timer*

|                                         |         |
|-----------------------------------------|---------|
| ANVEND                                  | KLIMA   |
| Normal, svovlniveau i brændstof <15 ppm | Moderat |

|                                     |                                   |                             |
|-------------------------------------|-----------------------------------|-----------------------------|
| PRODUKTANBEFALING 1                 | PRODUKTANBEFALING 2               | PRODUKTANBEFALING 3         |
| <b>Agrisynth LSP Ultra FE 5W-30</b> | <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> |

*Kontroller alle 10 timer, skift alle 250 timer*

**DIFFERENTIALE BEGRÆNSET SLIP MED TLS**  
Kapacitet: 13,7 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                                  |                          |                             |
|----------------------------------|--------------------------|-----------------------------|
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

*Kontroller alle 250 timer, skift alle 1500 timer*

**DIFFERENTIALE FOR** Standard MFWD  
Kapacitet: 14,4 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                                  |                          |                             |
|----------------------------------|--------------------------|-----------------------------|
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

*Kontroller alle 250 timer, skift alle 1500 timer*

**DIFFERENTIALE FORAN MED TLS OG DIFFERENTIALELÅS**  
Kapacitet: 10,8 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                                  |                          |                             |
|----------------------------------|--------------------------|-----------------------------|
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

*Kontroller alle 250 timer, skift alle 1500 timer*

# JOHN DEERE 7R SERIES 7215R IPM (EU) (2012-2016)



## GEAR

Kapacitet: 157 liter (AutoPowr), Kapacitet: 180 liter (CommandQuad), Kapacitet: 157 liter (IVT-transmission), Kapacitet: 180 liter (PowrQuad Plus/AutoQuad Plus)

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

#### PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

#### PRODUKTANBEFALING 3

**Kroontrak MTH 10W-30**

Kontroller alle 10 timer, skift alle 1500 timer

## KRAFTOVERFØRING

Kapacitet: 4 liter

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

#### PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

#### PRODUKTANBEFALING 3

**Kroontrak MTH 10W-30**

Kontroller alle 250 timer, skift alle 1500 timer

## NAVREDUKTION FORAN MED BREMSER

Kapacitet: 3,9 liter (hvert nav)

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

#### PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

#### PRODUKTANBEFALING 3

**Kroontrak MTH 10W-30**

Kontroller alle 250 timer, skift alle 1500 timer

## NAVREDUKTIONER FOR UDEN BREMSER

Kapacitet: 3,8 liter (hvert nav)

### ANVEND

Normal

### KLIMA

Middelhavsagtigt

#### PRODUKTANBEFALING 1

**Gearlube GL-5 85W-140**

#### PRODUKTANBEFALING 2

**Unigear LS GL-3/GL-5 85W-140**

Kontroller alle 250 timer, skift alle 1500 timer

### ANVEND

Normal

### KLIMA

Moderat

#### PRODUKTANBEFALING 1

**SP Gear 1011**

#### PRODUKTANBEFALING 2

**Syngear TDL 75W-90**

#### PRODUKTANBEFALING 3

**Gearlube HS GL-5 75W-90**

Kontroller alle 250 timer, skift alle 1500 timer

# JOHN DEERE 7R SERIES 7215R IPM (EU)

(2012-2016)



## SMØREPUNKTER/NIPLER

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

|                      |                                 |                              |
|----------------------|---------------------------------|------------------------------|
| PRODUKTANBEFALING 1  | PRODUKTANBEFALING 2             | PRODUKTANBEFALING 3          |
| <b>Labora Grease</b> | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Kontroller alle 250 timer, skift alle 1500 timer*

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                         |  |  |
|-------------------------|--|--|
| PRODUKTANBEFALING 1     |  |  |
| <b>Gear Grease EP 1</b> |  |  |

*Kontroller alle 250 timer, skift alle 1500 timer*

|        |       |
|--------|-------|
| ANVEND | KLIMA |
| Normal | Koldt |

|                         |  |  |
|-------------------------|--|--|
| PRODUKTANBEFALING 1     |  |  |
| <b>Gear Grease EP 0</b> |  |  |

*Kontroller alle 250 timer, skift alle 1500 timer*

## KØLESYSTEM

Kapacitet: 35 liter

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                       |                      |                               |
|-----------------------|----------------------|-------------------------------|
| PRODUKTANBEFALING 1   | PRODUKTANBEFALING 2  | PRODUKTANBEFALING 3           |
| <b>Coolant SP 15+</b> | <b>Coolant SP 12</b> | <b>Coolant -38 Organic NF</b> |

*Kontroller alle 10 timer, skift alle 2000 timer*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*