

JOHN DEERE 7R SERIES 7280R (EU) (2012-2016)



MOTOR John Deere PowerTech PSX Stage IIIb
Kapacitet: 27 liter

ANVEND	KLIMA
Biodiesel B20	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 125 timer

ANVEND	KLIMA
Normal, svovlniveau i brændstof <15 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 250 timer

DIFFERENTIALE BEGRÆNSET SLIP MED TLS
Kapacitet: 13,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer

DIFFERENTIALE FOR Standard MFWD
Kapacitet: 13,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer

DIFFERENTIALE FORAN MED TLS OG DIFFERENTIALELÅS
Kapacitet: 10,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer

JOHN DEERE 7R SERIES 7280R (EU) (2012-2016)



GEAR

Kapacitet: 155 liter (AutoPowr), Kapacitet: 155 liter (IVT-transmission)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 1500 timer

KRAFTOVERFØRING

Kapacitet: 4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer

NAVREDUKTION FORAN MED BREMSER

Kapacitet: 3,9 liter (hvert nav)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer

NAVREDUKTIONER FOR UDEN BREMSER

Kapacitet: 3,8 liter (hvert nav)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 250 timer, skift alle 1500 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Gearlube HS GL-5 75W-90

Kontroller alle 250 timer, skift alle 1500 timer

JOHN DEERE 7R SERIES 7280R (EU) (2012-2016)



SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Kontroller alle 250 timer, skift alle 1500 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gear Grease EP 1		

Kontroller alle 250 timer, skift alle 1500 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Gear Grease EP 0		

Kontroller alle 250 timer, skift alle 1500 timer

KØLESYSTEM

Kapacitet: 39,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Kontroller alle 10 timer, skift alle 2000 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.