

JOHN DEERE 7R SERIES 7215R (EU) (2012-2016)



ENGINE John Deere PowerTech PSX Stage 4i
Capacity: 24,5 liter

| USE | CLIMATE |
|---------------|----------|
| Biodiesel B20 | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------------|-----------------------------------|-----------------------------|
| Agrisynth LSP Ultra FE 5W-30 | Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40 |

Check every 10 hours, change every 125 hours

| USE | CLIMATE |
|-----------------------------------|----------|
| Normal, fuel sulfur level <15 ppm | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------------|-----------------------------------|-----------------------------|
| Agrisynth LSP Ultra FE 5W-30 | Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40 |

Check every 10 hours, change every 250 hours

DIFFERENTIAL FRONT Standard MFWD
Capacity: 14,4 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|----------------------------------|--------------------------|-----------------------------|
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 250 hours, change every 1500 hours

DIFFERENTIAL FRONT WITH TLS AND DIFFERENTIAL LOCK
Capacity: 10,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|----------------------------------|--------------------------|-----------------------------|
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 250 hours, change every 1500 hours

DIFFERENTIAL LIMITED SLIP FRONT WITH TLS
Capacity: 13,7 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|----------------------------------|--------------------------|-----------------------------|
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 250 hours, change every 1500 hours

JOHN DEERE 7R SERIES 7215R (EU) (2012-2016)



HUB REDUCTIONS FRONT WITH BRAKES

Capacity: 3,9 liter (each hub)

| USE | | CLIMATE |
|----------------------------------|--------------------------|-----------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 250 hours, change every 1500 hours

HUB REDUCTIONS FRONT WITHOUT BRAKES

Capacity: 3,8 liter (each hub)

| USE | | CLIMATE |
|------------------------------|-------------------------------------|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Check every 250 hours, change every 1500 hours

| USE | | CLIMATE |
|--------------------------|---------------------------|--------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Gearlube HS GL-5 75W-90 |

Check every 250 hours, change every 1500 hours

POWER TAKE OFF

Capacity: 4 liter

| USE | | CLIMATE |
|----------------------------------|--------------------------|-----------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 250 hours, change every 1500 hours

TRANSMISSION

Capacity: 157 liter (AutoPowr), Capacity: 180 liter (CommandQuad), Capacity: 157 liter (IVT transmission), Capacity: 180 liter (PowrQuad Plus/AutoQuad Plus)

| USE | | CLIMATE |
|----------------------------------|--------------------------|-----------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid Synth XHP Ultra | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 10 hours, change every 1500 hours

JOHN DEERE 7R SERIES 7215R (EU) (2012-2016)



GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 250 hours, change every 1500 hours

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Grease EP 1 | | |

Check every 250 hours, change every 1500 hours

| USE | | CLIMATE |
|--------------------------|--|---------|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Grease EP 0 | | |

Check every 250 hours, change every 1500 hours

COOLING SYSTEM

Capacity: 35 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Check every 10 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.