

JOHN DEERE 8020 SERIES 8320T (2003-2005)



ENGINE 8.1
Capacity: 25 liter

USE
Extended

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40

PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40

Check every 10 hours, change every 250 hours/ 12 months

TRANSAXLE/HYDRAULIC SYSTEM
Capacity: 246 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid Synth XHP Ultra

PRODUCT RECOMMENDATION 2
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30

Check every 10 hours, change every 1500 hours

GREASE POINTS/NIPPLES

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Labora Grease

PRODUCT RECOMMENDATION 2
Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3
MP Lithep Grease EP 2

Change every 50 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gear Grease EP 1

Change every 50 hours

USE
Normal

CLIMATE
Cold

PRODUCT RECOMMENDATION 1
Gear Grease EP 0

Change every 50 hours

JOHN DEERE 8020 SERIES 8320T (2003-2005)



COOLING SYSTEM

Capacity: 34 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.