

JOHN DEERE 8030 SERIES 8130 (2007-2009)



MOTOR John Deere PowerTech Plus - Tier IIIA

Kapacitet: 24 liter (1300 MFWD), Kapacitet: 25,5 liter (1300 MFWD + ikke-emission-certificeret motor), Kapacitet: 24,5 liter (1500 MFWD / ILS), Kapacitet: 28 liter (1500 MFWD / ILS + ikke-emission-certificeret motor)

ANVEND

Forlænget

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra FE 5W-30

PRODUKTANBEFALING 2

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 3

Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 375 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth LSP Ultra 10W-40

PRODUKTANBEFALING 2

Agrisynth LSP 10W-40

PRODUKTANBEFALING 3

Agrisynth MSP 10W-40

Kontroller alle 10 timer, skift alle 250 timer

DIFFERENTIALE FOR

Kapacitet: 13,6 liter (1300 MFWD), Kapacitet: 16,5 liter (1500 MFWD)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

NAVREDUKTIONER FOR

Kapacitet: 4 liter (med ILS), Kapacitet: 3,4 liter (MFWD)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Gearlube HS GL-5 75W-90

TRANSAKSEL/HYDRAULISK SYSTEM

Kapacitet: 160 liter (med ILS), Kapacitet: 150 liter (MFWD)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

JOHN DEERE 8030 SERIES 8130 (2007-2009)



SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gear Grease EP 1		

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Gear Grease EP 0		

KØLESYSTEM

Kapacitet: 40 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.