

JOHN DEERE 8R SERIES 8225R (NORDAMERIKA) (2009-2010)



MOTOR John Deere PowerTech Plus - Tier IIIA
Kapacitet: 25 liter

ANVEND	KLIMA
Udvidet, sulfoniveau i brændstof 0-1000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 375 timer

ANVEND	KLIMA
Udvidet, sulfoniveau i brændstof 1000-2000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 300 timer

ANVEND	KLIMA
Udvidet, sulfoniveau i brændstof 2000-5000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Normalt, sulfoniveau i brændstof 0-1000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 250 timer

ANVEND	KLIMA
Normalt, sulfoniveau i brændstof 1000-2000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA
Normalt, sulfoniveau i brændstof 2000-5000 ppm	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40

Kontroller alle 10 timer, skift alle 150 timer

JOHN DEERE 8R SERIES 8225R (NORDAMERIKA) (2009-2010)



DIFFERENTIALE FOR

Kapacitet: 13,6 liter (1300 MFWD), Kapacitet: 18,7 liter (1500 MFWD)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 250 timer, skift alle 1500 timer

NAVREDUKTIONER FOR

Kapacitet: 3,4 liter, Kapacitet: 3,8 liter (med ILS)

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 85W-140

PRODUKTANBEFALING 2

Unigear LS GL-3/GL-5 85W-140

Kontroller alle 250 timer, skift alle 1500 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

PRODUKTANBEFALING 3

Gearlube HS GL-5 75W-90

Kontroller alle 250 timer, skift alle 1500 timer

TRANSAKSEL/HYDRAULISK SYSTEM

Kapacitet: 150 liter, Kapacitet: 160 liter (med ILS)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 10 timer, skift alle 1500 timer

JOHN DEERE 8R SERIES 8225R (NORDAMERIKA) (2009-2010)



SMØREPUNKTER/NIPLER

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gear Grease EP 1		

Skift alle 50 timer

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1		
Gear Grease EP 0		

Skift alle 50 timer

KØLESYSTEM Kapacitet: 40 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.