

# JOHN DEERE 8R SERIES 8260R (NORDAMERIKA) 041001 -> 053100 (2013-2018)



**MOTOR** John Deere PowerTech PSX Stage IIb  
Kapacitet: 25 liter (1300 MFWD), Kapacitet: 28 liter (1500 MFWD), Kapacitet: 27,5 liter (med ILS)

|               |         |
|---------------|---------|
| ANVEND        | KLIMA   |
| Biodiesel B20 | Moderat |

|                                     |                                   |                             |
|-------------------------------------|-----------------------------------|-----------------------------|
| PRODUKTANBEFALING 1                 | PRODUKTANBEFALING 2               | PRODUKTANBEFALING 3         |
| <b>Agrisynth LSP Ultra FE 5W-30</b> | <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> |

Kontroller alle 10 timer, skift alle 125 timer/ 12 måneder

|                                          |         |
|------------------------------------------|---------|
| ANVEND                                   | KLIMA   |
| Normalt, svovlniveau i brændstof <15 ppm | Moderat |

|                                     |                                   |                             |
|-------------------------------------|-----------------------------------|-----------------------------|
| PRODUKTANBEFALING 1                 | PRODUKTANBEFALING 2               | PRODUKTANBEFALING 3         |
| <b>Agrisynth LSP Ultra FE 5W-30</b> | <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> |

Kontroller alle 10 timer, skift alle 250 timer/ 12 måneder

**DIFFERENTIALE FOR**  
Kapacitet: 13,6 liter (1300 MFWD), Kapacitet: 18,7 liter (1500 MFWD)

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                                  |                          |                             |
|----------------------------------|--------------------------|-----------------------------|
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3         |
| <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> |

Kontroller alle 250 timer, skift alle 1500 timer

**NAVREDUKTIONER FOR**  
Kapacitet: 3,8 liter (med ILS)

|        |                  |
|--------|------------------|
| ANVEND | KLIMA            |
| Normal | Middelhavsagtigt |

|                              |                                     |  |
|------------------------------|-------------------------------------|--|
| PRODUKTANBEFALING 1          | PRODUKTANBEFALING 2                 |  |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |  |

Kontroller alle 250 timer, skift alle 1500 timer

|        |         |
|--------|---------|
| ANVEND | KLIMA   |
| Normal | Moderat |

|                     |                           |                                |
|---------------------|---------------------------|--------------------------------|
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2       | PRODUKTANBEFALING 3            |
| <b>SP Gear 1011</b> | <b>Syngear TDL 75W-90</b> | <b>Gearlube HS GL-5 75W-90</b> |

Kontroller alle 250 timer, skift alle 1500 timer

# JOHN DEERE 8R SERIES 8260R (NORDAMERIKA) 041001 -> 053100 (2013-2018)

**TRANSAKSEL/HYDRAULISK SYSTEM**

Kapacitet: 165 liter, Kapacitet: 175 liter (med ILS)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Agrifluid Synth XHP Ultra**

PRODUKTANBEFALING 2

**Agrifluid HT-Plus**

PRODUKTANBEFALING 3

**Kroontrak MTH 10W-30***Kontroller alle 10 timer, skift alle 1500 timer***SMØREPUNKTER/NIPLER**

ANVEND

Normal

KLIMA

Middelhavssagtigt

PRODUKTANBEFALING 1

**Labora Grease**

PRODUKTANBEFALING 2

**Q5 MP Calcep Grease EP 2**

PRODUKTANBEFALING 3

**MP Lithep Grease EP 2***Skift alle 50 timer*

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gear Grease EP 1***Skift alle 50 timer*

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

**Gear Grease EP 0***Skift alle 50 timer***KØLESYSTEM**

Kapacitet: 41 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant SP 15+**

PRODUKTANBEFALING 2

**Coolant SP 12**

PRODUKTANBEFALING 3

**Coolant -38 Organic NF***Kontroller alle 10 timer, skift alle 2000 timer/ 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.