

# JOHN DEERE COMPACT TRACTORS 3320

## PIN (100001-) POWRREVERSER (2006-2012)



**ENGINE** Yanmar 3TNV88  
Capacity: 4,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth LSP 10W-40</b>	<b>Agrisynth MSP 10W-40</b>

*Check every 10 hours, change every 200 hours/ 12 months*

**DIFFERENTIAL FRONT**  
Capacity: 4,5-5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 50 hours, change every 600 hours*

**TRANSAXLE/HYDRAULIC SYSTEM** PowrReverser  
Capacity: 23,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 10 hours, change every 400 hours*

### GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 50 hours*

**COOLING SYSTEM**  
Capacity: 7 liter (+ cabin), Capacity: 5,3 liter (Without cabin)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Check every 10 hours, change every 2000 hours/ 24 months*

# JOHN DEERE COMPACT TRACTORS 3320 PIN (100001-) POWRREVERSER (2006-2012)



## AIRCONDITIONING

Capacity: 1,3 kg

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*