

JOHN DEERE PROFESSIONAL UTILITY MOWERS 3225/3235B FAIRWAY MOWER PIN (010001-)(2000-2005)



ENGINE Yanmar 3TNE84-EJFE
Capacity: 5,5 liter, Filter capacity: 0,5 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Multifleet SHPD 10W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 15W-40
--	--	--

Check every 5 hours, change every 100 hours

USE First change only	CLIMATE Moderate
---------------------------------	----------------------------

PRODUCT RECOMMENDATION 1 Kroontrak MTH 10W-30	PRODUCT RECOMMENDATION 2 Multifleet SHPD 10W-40	PRODUCT RECOMMENDATION 3 Multifleet SHPD 15W-40
--	--	--

Change every 50 hours

TRANSAXLE HYDROSTATIC
Capacity: 45,4 liter

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Agrifluid Synth XHP Ultra	PRODUCT RECOMMENDATION 2 Agrifluid HT-Plus	PRODUCT RECOMMENDATION 3 Kroontrak MTH 10W-30
---	---	--

Check every 50 hours, change every 500 hours

GREASE POINTS/NIPPLES

USE Normal	CLIMATE Mediterranean
----------------------	---------------------------------

PRODUCT RECOMMENDATION 1 Labora Grease	PRODUCT RECOMMENDATION 2 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 3 MP Lithep Grease EP 2
---	--	---

Check every 25 hours

USE Normal	CLIMATE Moderate
----------------------	----------------------------

PRODUCT RECOMMENDATION 1 Gear Grease EP 1		
--	--	--

Check every 25 hours

USE Normal	CLIMATE Cold
----------------------	------------------------

PRODUCT RECOMMENDATION 1 Gear Grease EP 0		
--	--	--

Check every 25 hours

JOHN DEERE PROFESSIONAL UTILITY MOWERS 3225/3235B FAIRWAY MOWER PIN (010001-)(2000-2005)



COOLING SYSTEM

Capacity: 7,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 5 hours, change every 2000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.