

JOHN DEERE SERIE 1100 1174 SII (1991-1992)



MOTOR CD 6359 TZ003
Kapacitet: 13 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 40	Multifleet SCD 30	

Kontroller alle 10 timer, skift alle 200 timer/ 12 måneder

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SHPD 15W-40

Kontroller alle 10 timer, skift alle 200 timer/ 12 måneder

ANVEND		KLIMA
Normal		Koldt
PRODUKTANBEFALING 1		
Multifleet SCD 10W		

Kontroller alle 10 timer, skift alle 200 timer/ 12 måneder

CYLINDER DREV REDUKTION
Kapacitet: 1,9 liter

ANVEND		KLIMA
Normal		Middelhavsagtigt
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140

Kontroller alle 12 måneder/ 200 timer, skift alle 800 timer

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 1011	SP Gear 5015	Syngear TDL 75W-90

Kontroller alle 12 måneder/ 200 timer, skift alle 800 timer

JOHN DEERE SERIE 1100 1174 SII (1991-1992)



GEAR MANUEL 4/1

Kapacitet: 6,6 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

PRODUKTANBEFALING 3

Gearlube GL-5 85W-140

Kontroller alle 12 måneder/ 200 timer, skift alle 800 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Syngear TDL 75W-90

Kontroller alle 12 måneder/ 200 timer, skift alle 800 timer

KÆDEDREV SKÆREPLATFORM

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

PRODUKTANBEFALING 3

Gearlube GL-5 85W-140

Kontroller alle 12 måneder/ 200 timer, skift alle 800 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Syngear TDL 75W-90

Kontroller alle 12 måneder/ 200 timer, skift alle 800 timer

NAVREDUKTIONER FOR

Kapacitet: 2,2 liter

ANVEND

Normal

KLIMA

Middelhavsagtigt

PRODUKTANBEFALING 1

Gearlube GL-5 80W-90

PRODUKTANBEFALING 2

Unigear HS GL-3/GL-5 80W-90

PRODUKTANBEFALING 3

Gearlube GL-5 85W-140

Kontroller alle 12 måneder/ 200 timer, skift alle 800 timer

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

SP Gear 5015

PRODUKTANBEFALING 3

Syngear TDL 75W-90

Kontroller alle 12 måneder/ 200 timer, skift alle 800 timer

JOHN DEERE SERIE 1100 1174 SII (1991-1992)



HYDRAULISK SYSTEM

Kapacitet: 20 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Skift alle 400 timer

HYDRAULISK SYSTEM HYDROSTATISK SPOLEDREV

Kapacitet: 10 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Skift alle 400 timer

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT-Plus

PRODUKTANBEFALING 3

Kroontrak MTH 10W-30

Kontroller alle 12 måneder/ 200 timer

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 10 timer

KØLESYSTEM

Kapacitet: 30 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 12 måneder/ 200 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.