

# JOHN DEERE TELESCOPIC HANDLERS

## 3420 (2004-2006)



**ENGINE** John Deere 4045 HZ275  
Capacity: 13 liter, Filter capacity: 1 liter

**USE**  
Extended

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Agrisynth LSP 10W-40**

**PRODUCT RECOMMENDATION 2**  
**Agrisynth MSP 10W-40**

**PRODUCT RECOMMENDATION 3**  
**Agirdiesel MSP 15W-40**

*Check every 10 hours, change every 500 hours*

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Kroontrak CVT 10W-40**

**PRODUCT RECOMMENDATION 2**  
**Agrisynth MSP 10W-40**

**PRODUCT RECOMMENDATION 3**  
**Agirdiesel MSP 15W-40**

*Check every 10 hours, change every 250 hours/ 12 months*

**DIFFERENTIAL FRONT**  
Capacity: 7 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Agrifluid Synth XHP Ultra**

**PRODUCT RECOMMENDATION 2**  
**Agrifluid HT-Plus**

**PRODUCT RECOMMENDATION 3**  
**Kroontrak MTH 10W-30**

*Check every 50 hours, change every 1000 hours/ 12 months*

**DIFFERENTIAL REAR**  
Capacity: 7,1 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Agrifluid Synth XHP Ultra**

**PRODUCT RECOMMENDATION 2**  
**Agrifluid HT-Plus**

**PRODUCT RECOMMENDATION 3**  
**Kroontrak MTH 10W-30**

*Check every 50 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS FRONT**  
Capacity: 0,8 liter

**USE**  
Normal

**CLIMATE**  
Moderate

**PRODUCT RECOMMENDATION 1**  
**Agrifluid Synth XHP Ultra**

**PRODUCT RECOMMENDATION 2**  
**Agrifluid HT-Plus**

**PRODUCT RECOMMENDATION 3**  
**Kroontrak MTH 10W-30**

*Check every 50 hours, change every 1000 hours/ 12 months*

# JOHN DEERE TELESCOPIC HANDLERS

## 3420 (2004-2006)



### HUB REDUCTIONS REAR

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 50 hours, change every 1000 hours/ 12 months*

### TRANSMISSION

Capacity: 19 liter (Powershift), Capacity: 18,5 liter (Shuttle Command)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 10 hours, change every 1000 hours/ 12 months*

### HYDRAULIC SYSTEM

Capacity: 180 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 10 hours, change every 1000 hours/ 12 months*

# JOHN DEERE TELESCOPIC HANDLERS

## 3420 (2004-2006)



### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 50 hours*

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gear Grease EP 1</b>		

*Check every 50 hours*

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
<b>Gear Grease EP 0</b>		

*Check every 50 hours*

### COOLING SYSTEM

Capacity: 35 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 2000 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*