

# JOHN DEERE X SERIES LAWN & GARDEN TRACTORS GX345 PIN (105001-) (2002-2005)

**ENGINE FD611V**

Capacity: 1,9 liter, Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Multifleet SHPD 10W-40***Check every 10 hours, change every 200 hours/ 12 months*

USE	CLIMATE
First change only	Moderate

## PRODUCT RECOMMENDATION 1

**Asyntho 5W-30**

## PRODUCT RECOMMENDATION 2

**Multifleet SHPD 10W-40***Change every 50 hours***TRANSAXLE HYDROSTATIC**

Capacity: 4,7 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

## PRODUCT RECOMMENDATION 2

**Agrifluid HT-Plus***Check every 50 hours, change every 250 hours***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Labora Grease**

## PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

## PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Check every 50 hours***COOLING SYSTEM**

Capacity: 3,1 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

## PRODUCT RECOMMENDATION 2

**Coolant -26***Check every 10 hours, change every 500 hours/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.