

KIOTI/DAEDONG EX EX45 4A220LXM



MOTOR 4A220LXM
Kapacitet: 8 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 100 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SHPD 15W-40

PRODUKTANBEFALING 2

Multifleet SCD 20W-20

Skift alle 100 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Multifleet SHPD 10W-40

Skift alle 100 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 100 timer

ANVEND	KLIMA
Første skift kun	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 50 timer

ANVEND	KLIMA
Første skift kun	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SHPD 15W-40

PRODUKTANBEFALING 2

Multifleet SCD 20W-20

Skift alle 50 timer

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Multifleet SHPD 10W-40

Skift alle 50 timer

KIOTI/DAEDONG EX EX45 4A220LXM



ANVEND		KLIMA
Første skift kun		Arktisk
PRODUKTANBEFALING 1		
Multifleet SCD 10W		
Skift alle 50 timer		

DIFFERENTIALE FOR		
Kapacitet: 7,5 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Skift alle 400 timer		

ANVEND		KLIMA
Første skift kun		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Skift alle 50 timer		

TRANSAKSEL MANUEL		
Kapacitet: 52 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Skift alle 200 timer		

ANVEND		KLIMA
Første skift kun		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Skift alle 50 timer		

SMØREPUNKTER/NIPLER		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Skift alle 50 timer		

KIOTI/DAEDONG EX EX45 4A220LXM



KØLESYSTEM

Kapacitet: 8,7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.