

**KRONE BIG X BIG X 800 784.938->791.255****ENGINE** Mercedes-Benz OM460LA

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP 10W-40***Check every 10 hours, change every 400 hours/ 12 months***ENGINE** Mercedes-Benz OM926LA

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP 10W-40***Check every 10 hours, change every 400 hours/ 12 months***FAN GEAR**

Capacity: 1,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 100 hours, change every 1000 hours***LOWER ROLLER GEAR**

Capacity: 5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 100 hours, change every 1000 hours***LOWER ROLLER GEAR UPPER TOWER**

Capacity: 1,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Check every 100 hours, change every 1000 hours*

**POWER TAKE OFF**

Capacity: 10-23 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Abacot MEP Synth 220***Check every 100 hours, change every 1000 hours***TOWER GEARBOX ON THE UPPER DISCHARGE CHUTE**

Capacity: 1 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 100 hours, change every 1000 hours***TRANSFERBOX**

Capacity: 8 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Abacot MEP Synth 220***Check every 100 hours, change every 1000 hours***UPPER ROLLER GEAR**

Capacity: 3,6 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 100 hours, change every 1000 hours***HYDRAULIC SYSTEM**

Capacity: 150 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Perlus H 46****PRODUCT RECOMMENDATION 2****Perlus AF 46***Check every 10 hours, change every 500 hours/ 12 months*

**CENTRAL LUBRICATION SYSTEM** Vogel

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

**COOLING SYSTEM**

Capacity: 60 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 11</b>		

*Check every 10 hours, change every 3000 hours*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*