KRONE ZX ZX 450 GD 896.419->



CONVEYOR DRUM GEARBOX Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 10 hours, change every 200 hours/ 12 months

DISCHARGE ROLLER DRIVE FROM	NT	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check over 10 hours shares ever 200 hours / 12 months		

Check every 10 hours, change every 200 hours/ 12 months

DISCHARGE ROLLER DRIVE REAR Capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 10 hours, change every 200 hours/ 12 months

FLOOR CONVEYOR DRIVE Capacity: 1,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 10 hours, change ever	y 200 hours/ 12 months	,

MAIN GEARBOX Capacity: 4,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Charle avant 10 hours, change avant 200 hours/12 months		

Check every 10 hours, change every 200 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

KRONE ZX ZX 450 GD 896.419->



information contained herein is subject to changes without notification.