KRONE ZX ZX 550 GL 896.419->



| CONVEYOR DRUM GEARBOX Capacity: 9 liter | | |
|--|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 10 hours, change every 200 hours/ 12 months

| FLOOR CONVEYOR DRIVE Capacity: 1,1 liter | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Check every 10 hours, change ever | y 200 hours/ 12 months | ' |

MAIN GEARBOX
Capacity: 4,3 liter

USE

Normal

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

MAIN GEARBOX
Capacity: 4,3 liter

CLIMATE
Moderate

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 10 hours, change every 200 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.