

KUBOTA B SERIER B1700, B1700 HST/BISPEED (1993 OG EFTER)



MOTOR Kubota D905-D10
Kapacitet: 3 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 30	HDX 30	

Skift alle 200 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 20W-20	HDX 20W-20	

Skift alle 200 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SCD 10W

Skift alle 200 timer

DIFFERENTIALE FOR (4x4)
Kapacitet: 3,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT-Plus		

Kontroller alle 50 timer, skift alle 300 timer

DIFFERENTIALE FOR TO-TRINS GEAR
Kapacitet: 4,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT-Plus		

Kontroller alle 50 timer, skift alle 300 timer

KUBOTA B SERIER B1700, B1700

HST/BISPEED (1993 OG EFTER)



TRANSAKSEL HYDROSTATISK/HYDRAULISK SYSTEM

Kapacitet: 12 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus*Skift alle 300 timer*

TRANSAKSEL/HYDRAULISK SYSTEM

Kapacitet: 11 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT-Plus*Skift alle 300 timer*

SMØREPUNKTER/NIPLER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2*Kontroller alle 50 timer*

KØLESYSTEM

Kapacitet: 3,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26*Skift alle 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.