

KUBOTA G/GR G23 LD (2009 OG EFTER)



MOTOR Kubota D902-E3-GT
Kapacitet: 3,1 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 200 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SHPD 15W-40

PRODUKTANBEFALING 2

Multifleet SCD 20W-20

Skift alle 200 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Multifleet SHPD 10W-40

Skift alle 200 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1

Multifleet SCD 10W

Skift alle 200 timer

ANVEND	KLIMA
Første skift kun	Tropisk

PRODUKTANBEFALING 1

Multifleet SCD 30

Skift alle 50 timer

ANVEND	KLIMA
Første skift kun	Middelhavsagtigt

PRODUKTANBEFALING 1

Multifleet SHPD 15W-40

PRODUKTANBEFALING 2

Multifleet SCD 20W-20

Skift alle 50 timer

ANVEND	KLIMA
Første skift kun	Moderat

PRODUKTANBEFALING 1

Kroontrak MTH 10W-30

PRODUKTANBEFALING 2

Multifleet SHPD 10W-40

Skift alle 50 timer

KUBOTA G/GR G23 LD (2009 OG EFTER)



ANVEND		KLIMA
Første skift kun		Arktisk
PRODUKTANBEFALING 1		
Multifleet SCD 10W		
<i>Skift alle 50 timer</i>		

GEARKASSE SLÅMASKINENS PLATFORME		
Kapacitet: 1,9 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Agrifluid HT		
<i>Skift alle 150 timer</i>		

ANVEND		KLIMA
Første skift kun		Moderat
PRODUKTANBEFALING 1		
Agrifluid HT		
<i>Skift alle 50 timer</i>		

TRANSAKSEL HYDROSTATISK/HYDRAULISK SYSTEM		
Kapacitet: 11 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Agrifluid HT		
<i>Skift alle 400 timer</i>		

KØLESYSTEM		
Kapacitet: 3,1 liter		
ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	
<i>Skift alle 24 måneder</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.