PRODUCT RECOMMENDATION

KUBOTA RIDE-ON GRASS CUTTING MACHINES T1600 PETROL

ENGINE

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
HDX 30		
Change every 100 hours		

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
HDX 20W-20		
Change every 100 hours		

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Change every 100 hours		

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Change every 100 hours		

USE		CLIMATE
Initial service		Tropical
PRODUCT RECOMMENDATION 1		
HDX 30		
Change every 50 hours		

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
HDX 20W-20		
Change every 50 hours		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		
Change every 50 hours		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KUBOTA RIDE-ON GRASS CUTTING MACHINES T1600 PETROL

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Change every 50 hours		

GEARBOX MOWER DECKS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

TRANSMISSION

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		
Change every 300 hours		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367