

KUBOTA L SERIEN L3750 (1985-1989)



MOTOR Kubota D2302-DI-L
Kapacitet: 9 liter

ANVEND	KLIMA
Normal	Tropisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 30	HDX 30	

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA
Normal	Middelhavsagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 20W-20	HDX 20W-20	

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	

Kontroller alle 10 timer, skift alle 200 timer

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Multifleet SCD 10W	HDX 10W	

Kontroller alle 10 timer, skift alle 200 timer

DIFFERENTIALE FOR (4x4)
Kapacitet: 5,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Kontroller alle 100 timer, skift alle 300 timer

TRANSAKSEL/HYDRAULISK SYSTEM 8/8
Kapacitet: 43 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Agrifluid HT		

Kontroller alle 150 timer, skift alle 300 timer

KUBOTA L SERIEN L3750 (1985-1989)



SERVOSTYRING

Kapacitet: 2,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid HT

Skift alle 400 timer

SMØREPUNKTER/NIPLER ANDRE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 50 timer

SMØREPUNKTER/NIPLER HJULLEJER FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 300 timer

SMØREPUNKTER/NIPLER KOBLINGSUDRYKKERLEJE

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Labora Grease

PRODUKTANBEFALING 2

Q5 MP Calcep Grease EP 2

PRODUKTANBEFALING 3

MP Lithep Grease EP 2

Kontroller alle 100 timer

KØLESYSTEM

Kapacitet: 7,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

PRODUKTANBEFALING 2

Coolant -26

Kontroller alle 10 timer, skift alle 400 timer

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.