## KUBOTA L SERIES L3001 (1980-1985)



ENGINE Capacity: 7 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	HDX 30	
Check every 10 hours, change every 75 ho	DURS	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 20W-20	HDX 20W-20	
Check every 10 hours, change every 75 ho	Durs	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	
Check every 10 hours, change every 75 ho	ours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W	HDX 10W	
Check every 10 hours, change every 75 ho	ours	
<b>DIFFERENTIAL FRONT</b> (4x4) Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate

Change every 300 hours

**Agrifluid HT-Plus** 

**PRODUCT RECOMMENDATION 1** 

HUB REDUCTIONS FRONT (4x4) Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W
	I	

PRODUCT RECOMMENDATION 2

SP Gear 5015

Change every 300 hours

**PRODUCT RECOMMENDATION 3** 

Gearlube GL-4 80W

## KUBOTA L SERIES L3001 (1980-1985)



TRANSAXLE/HYDRAULIC SYSTEM Capacity: 26 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-1 80W-90	
01 1 101 1 0001	

Check every 10 hours, change every 300 hours

POWER STEERING Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 20W-20	Multifleet SCD 10W	HDX 20W-20

Check every 300 hours

GREASE POINTS/NIPPLES CLUTCH RELEASE BEARING		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 300 hours

GREASE POINTS/NIPPLES OTHE	RS	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Chaolic avera 50 hours		

Check every 50 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT	
	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
	PRODUCT RECOMMENDATION 2

Check every 300 hours

## KUBOTA L SERIES L3001 (1980-1985)



COOLING SYSTEM Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 12 months

STEERING BOX Capacity: 0,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	SP Gear 5015	Gearlube GL-4 80W

Check every 150 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.