

KUBOTA M SERIES M105X (2005-2007)

ENGINE Kubota V3800-TIE2
Capacity: 10,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 250 hours*

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SCD 20W-20*Change every 250 hours*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30*Change every 250 hours*

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 250 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Tropical |

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 50 hours*

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

PRODUCT RECOMMENDATION 3

Multifleet SCD 20W-20*Change every 50 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30*Change every 50 hours*

KUBOTA M SERIES M105X (2005-2007)

| USE | | CLIMATE |
|------------------------------|--|---------|
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |
| <i>Change every 50 hours</i> | | |

| DIFFERENTIAL FRONT Capacity: 7 liter | | |
|-----------------------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| <i>Change every 600 hours</i> | | |

| USE | | CLIMATE |
|------------------------------|--|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| <i>Change every 50 hours</i> | | |

| GEAR CASE FRONT Capacity: 3,5 liter | | |
|----------------------------------------|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| <i>Change every 600 hours</i> | | |

| USE | | CLIMATE |
|------------------------------|--|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| <i>Change every 50 hours</i> | | |



KUBOTA M SERIES M105X (2005-2007)**TRANSMISSION**

Capacity: 60 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT***Change every 600 hours***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT***Change every 50 hours***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT****COOLING SYSTEM**

Capacity: 9 liter (Radiator + engine), Capacity: 1,1 liter (Recovery tank)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.