

KUBOTA M SERIER M110GX (2013 OG EFTER)



MOTOR Kubota V3800-TIE4
Kapacitet: 10,5 liter

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth MSP 10W-40

PRODUKTANBEFALING 2

Agridiesel MSP 15W-40

PRODUKTANBEFALING 3

Dieselfleet LSP Ultra 10W-30

Skift alle 50 timer

ANVEND

Normalt, svovlniveau i brændstof <15 ppm

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrisynth MSP 10W-40

PRODUKTANBEFALING 2

Agridiesel MSP 15W-40

PRODUKTANBEFALING 3

Dieselfleet LSP Ultra 10W-30

Kontroller alle 10 timer, skift alle 400 timer

DIFFERENTIALE FOR

Kapacitet: 7 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

PRODUKTANBEFALING 2

Agrifluid HT

Skift alle 600 timer

GEAR

Kapacitet: 65 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

Skift alle 600 timer

ANVEND

Første skift kun

KLIMA

Moderat

PRODUKTANBEFALING 1

Agrifluid Synth XHP Ultra

Skift alle 50 timer

KUBOTA M SERIER M110GX (2013 OG EFTER)



NAVREDUKTIONER FOR

Kapacitet: 3,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Agrifluid Synth XHP Ultra	Agrifluid HT	

Skift alle 600 timer

SMØREPUNKTER/NIPLER

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Skift alle 50 timer

KØLESYSTEM

Kapacitet: 9,6 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant -38 Organic NF	Coolant -26	

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.