

# KUBOTA M SERIES M130X WITH EGR (2010 AND AFTER)



**ENGINE** Kubota V6108  
Capacity: 14,6 liter

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agridiesel CRD+ 15W-40</b>	<b>Multifleet SCD 30</b>

*Change every 50 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	
<b>Multifleet SCD 20W-20</b>	

*Change every 50 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth LSP 10W-40</b>	<b>Kroontrak CVT 10W-40</b>

*Change every 50 hours*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1	
<b>Multifleet SCD 10W</b>	

*Change every 50 hours*

USE	CLIMATE
Normal, fuel sulfur level < 500 ppm	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Agridiesel CRD+ 15W-40</b>	<b>Multifleet SCD 30</b>

*Change every 400 hours*

USE	CLIMATE
Normal, fuel sulfur level < 500 ppm	Mediterranean

PRODUCT RECOMMENDATION 1	
<b>Multifleet SCD 20W-20</b>	

*Change every 400 hours*

USE	CLIMATE
Normal, fuel sulfur level < 500 ppm	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth LSP 10W-40</b>	<b>Kroontrak CVT 10W-40</b>

*Change every 400 hours*

# KUBOTA M SERIES M130X WITH EGR (2010 AND AFTER)



USE		CLIMATE
Normal, fuel sulfur level < 500 ppm		Arctic
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		
<i>Change every 400 hours</i>		

DIFFERENTIAL FRONT Capacity: 12 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT</b>		
<i>Change every 600 hours</i>		

GEAR CASE FRONT Capacity: 4,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT</b>		
<i>Change every 600 hours</i>		

TRANSMISSION Capacity: 60 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT</b>		
<i>Change every 600 hours</i>		

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT</b>		
<i>Change every 50 hours</i>		



# KUBOTA M SERIES M130X WITH EGR (2010 AND AFTER)



## HYDRAULIC BRAKE SYSTEM

Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT</b>		

## COOLING SYSTEM

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*