PRODUCT RECOMMENDATION

LAMBORGHINI 600/700 700 (1988-1992)

ENGINE Perkins 1000.3-AT
Capacity: 7,1 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1
Multifleet SCD 40

Check every 10 hours, change every 150 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1
Multifleet SCD 30

Check every 10 hours, change every 150 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Multifleet SHPD 15W-40

Check every 10 hours, change every 150 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1
Multifleet SCD 20W-20

Check every 10 hours, change every 150 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT

Check every 150 hours, change every 1200 hours

HUB REDUCTIONS FRONT (4x4)
Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT

Check every 150 hours, change every 1200 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

LAMBORGHINI 600/700 700 (1988-1992)

POWER TAKE OFF FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

TRANSAXLE/HYDRAULIC SYSTEM 12/12

Capacity: 28 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 150 hours, change every 2400 hours

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
ATF Dexron II-D	**Perlus Biosynth 46**	**Perlus H 46**

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	**Caliplex HD Grease EP 2**	

Check every 50 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	**Caliplex HD Grease EP 2**	

Change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367