

# LAMBORGHINI PREMIUM 1300 PREMIUM

## (1995-2003)



**ENGINE** Perkins 1000.6-W1  
Capacity: 15 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 150 hours/ 12 months*

**DIFFERENTIAL FRONT (4x4)**  
Capacity: 10,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

*Check every 150 hours, change every 1200 hours/ 12 months*

**HUB REDUCTIONS FRONT (4x4)**  
Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

*Check every 150 hours, change every 1200 hours/ 12 months*

**POWER TAKE OFF**  
Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

*Check every 150 hours, change every 1200 hours*

**TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 24/12**  
Capacity: 75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

*Check every 150 hours, change every 1200 hours/ 12 months*

# LAMBORGHINI PREMIUM 1300 PREMIUM

(1995-2003)



## HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**ATF Dexron II-D***Check every 300 hours, change every 24 months*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Q7 MP Calcep Grease WR 2**

PRODUCT RECOMMENDATION 2

**Caliplex HD Grease EP 2***Check every 50 hours*

## COOLING SYSTEM

Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -33 MPG***Check every 10 hours, change every 2400 hours/ 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.