PRODUCT RECOMMENDATION

LAMBORGHINI R R 1056, -DT (1978-1981)

ENGINE R 986/3
Capacity: 15 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	**HDX 40**	

Check every 10 hours, change every 125 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
HDX 30		

Check every 10 hours, change every 125 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 15W-40	**HDX 20W-20**	

Check every 10 hours, change every 125 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	**Kroontrak MTH 10W-30**	**Agrifluid HT**

Check every 125 hours, change every 1000 hours

HUB REDUCTIONS FRONT (4x4)
Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	**Kroontrak MTH 10W-30**	**Agrifluid HT**

Check every 125 hours, change every 1200 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

LAMBORGHINI R R 1056, -DT (1978-1981)

TRANSAXLE/HYDRAULIC SYSTEM 12/3
Capacity: 66 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	**Kroontrak MTH 10W-30**	**Agrifluid HT**

Check every 125 hours, change every 3000 hours

HYDRAULIC BRAKE SYSTEM
Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF-A		

Check every 125 hours

POWER STEERING
Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
ATF Dexron II-D	**Perlus Biosynth 46**	**Perlus H 46**

Check every 125 hours, change every 1000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	**Caliplex HD Grease EP 2**	

Check every 50 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q7 MP Calcep Grease WR 2	**Caliplex HD Grease EP 2**	

Change every 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367